

**(PART-B)**

**REVISED FINANCIAL BID**

**Supply, Installation and Commissioning of CCTV Surveillance System**

Sl. No.	Description of Items	Particulars	Unit	Rate per Unit (in Rs.)	Make & Model
1	Bullet Camera	2MP 1/2.8" CMOS image sensor, low luminance, and high definition image, Outputs max. 2MP (1920 × 1080) @25/30 fps, Support Triple Stream, Built-in IR LED, and the max. illumination distance is 60 m – 80 m, Rotation mode, WDR, 3D NR, HLC, BLC, digital watermarking, Intelligent monitoring: Intrusion, tripwire, Alarm: 1 in, 1 out; audio: 1 in, 1 out; supports max. 256 GB micro SD card, 12V DC/PoE power supply. IP67, Motorized vari-focal lens 2.7mm–13.5mm	01 No.		
		4MP, 1/3" CMOS image sensor, low illuminance, high image definition, Outputs 4MP (2560 × 1440)@25/30 fps, max. supports 4MP (2688 × 1520) @20 fps, Support Triple Stream, Built-in IR LED, max IR distance: 60 m – 80 m, Rotation mode, WDR, 3D NR, HLC, BLC, digital watermarking, Intelligent detection: Intrusion, tripwire, Alarm: 1 in, 1 out; audio: 1 in, 1 out; supports max. 256 GB Micro SD card, 12V DC/PoE power supply, IP67 protection, Motorized vari-focal lens 2.7mm–13.5mm	01 No.		
2	Dome Camera	2MP 1/2.8" CMOS image sensor, low luminance, and high definition image, Outputs max. 2MP (1920 × 1080) @25/30 fps, Support Triple Stream, Built-in IR LED, and the max. illumination distance is 40 m, Rotation mode, WDR, 3D NR, HLC, BLC, digital watermarking, Intelligent monitoring: Intrusion, tripwire, Alarm: 1 in, 1 out; audio: 1 in, 1 out; supports max. 256 G micro SD card.12V DC/PoE power supply.IP67, IK10 protection. Motorized vari-focal lens 2.7mm–13.5mm	01 No.		

  
21/12/23

3	NVR – 8 CH	Video Channel 8 Input, H.264, H.265, Smart H.264+, and Smart H.265+. H.265 auto switch, Max. decoding capability: 8 × 1080p@30 fps., VGA/HDMI simultaneous video output, maximum resolution of HDMI is 4K, AI by Camera: Face detection, perimeter protection, IVS, people counting, heat map, and SMD, 2 SATA III ports, up to 10 TB for a single HDD, Access: 160 Mbps; Storage: 160 Mbps; Forward: 64 Mbps, Resolution- 8MP; 6MP; 5MP; 4MP; 3MP; 1080p; 720p; D1, 1 × RJ-45, 10/100/1000 Mbps self-adaptive Ethernet port, Power Supply - 12 V DC, 4 A,	01 No.		
4	NVR – 16 CH	Video Channel 16 Input, H.264, H.265, Smart H.264+, and Smart H.265+. H.265 auto switch, Max. decoding capability: 8 × 1080p@30 fps., VGA/HDMI simultaneous video output, maximum resolution of HDMI is 4K, AI by Camera: Face detection, perimeter protection, IVS, people counting, heat map, and SMD, 2 SATA III ports, up to 10 TB for a single HDD, Access: 160 Mbps; Storage: 160 Mbps; Forward: 64 Mbps, Resolution- 8MP; 6MP; 5MP; 4MP; 3MP; 1080p; 720p; D1, 1 × RJ-45, 10/100/1000 Mbps self-adaptive Ethernet port, Power Supply - 12 V DC, 4 A	01 No.		
5	NVR – 32 CH	Video Channel 32 Input, H.264, H.265, Smart H.264+, and Smart H.265+. H.265 auto switch, Max. decoding capability: 8 × 1080p@30 fps., VGA/HDMI simultaneous video output, maximum resolution of HDMI is 4K, AI by Camera: Face detection, perimeter protection, IVS, people counting, heat map, and SMD, 2 SATA III ports, up to 10 TB for a single HDD, Access: 160 Mbps; Storage: 160 Mbps; Forward: 64 Mbps, Resolution- 8MP; 6MP; 5MP; 4MP; 3MP; 1080p; 720p; D1, 1 × RJ-45, 10/100/1000 Mbps self-adaptive Ethernet port, Power Supply - 12 V DC, 4 A	01 No.		
6	HDD	8 TB Surveillance HDD	01 No.		

  
 21/12/23

7	Monitor	Diagonal Size-32 Inches, Resolution -FHD (1920 x 1080), Contrast Ratio 5000:1, Brightness-400, Connectivity-2HDMI, USB & RJ 45	01 No.		
8	Ethernet PoE Switch	8 port full giga POE with 2 Uplink Port 10/100/1000 Power watts 120 W	01 No.		
9	UPS	1KVA Online UPS with 1Hrs. backup with external Battery & stand	01 No.		
10	Power cable	3 Crore 1.5mm Power cable with laying	Per Mtr.		
11	Cabling	UTP Cable laying through PVC Pipe with ISI Standards (As per the requirement)	Per Mtr		
12	Cable	Cat 6 UTP cable (305 Mtr.)	1 Box		
13	Networking Rack	9U wall mount Rack with all accessories for rack mounting	01 No.		
14	Installation	Labour charges for cabling with PVC pipe / and accessories and also Installation, Integration and handholding & support services	Lump sum per location		
		if required, digging with filling GI pipe for cable laying	Per Mtr.		
15	Helpdesk Support	Help Desk Operator should be available from Monday to Saturdays from 10.00 AM to 10.00 PM.	Man per Month		
<b>Total</b>					

**N.B :** i. The total of item wise quoted rate will be taken together to arrive at the lowest rate.

ii. The rates quoted shall be inclusive of GST and all other statutory taxes, levies, cess etc.

Date:-

**Signature of the Tenderer  
(Name & Address of the Tenderer)  
Seal**

  
21/2/23